Occhio

Sento sospeso up
cutsheet

LED suspended luminaire with double sided light output, luminous power 32W (version with chrome finish 26W). Ratio of up and down light adjustable.
Lighting effect changeable via optional inserts.

Up-version with height adjustment
LED suspended luminaire freely height adjustable and high base incl. power supply unit (converter) for mounting on fixed ceiling, connection to 230V. Remote dimmable via trailing edge phase-cut dimmer or with gestures "touchless fading" on the head.

Up-version with fixed length
LED suspended luminaire with a fixed adjustable height and high base incl. power supply unit (converter) for mounting on fixed ceiling, connection to 230V.
Remote dimmable via trailing edge phase-cut dimmer or with gestures "touchless fading" on the head.





materials luminaire
aluminium, steel chrome-plated, painted or anodised, plastic

materials inserts
glass, optical plastic

surface head
chrome, matt chrome, glossy white (bianco), matt white

on request
glossy black (nero), matt black

freely height adjustable
only variable version

length
variable
500 – 2000 mm
fix
max. 3500 mm

weight
variable 2,6 kg
fix 2,1 kg

dimming function
by integrated touchless sensor in head or with trailing edge phase-cut dimmer

ECG (driver)
integrated,for use with 230 V AC

Occhio »next generation« LED

					LED high color		LED high flux		
average lifetime	t	> 50.000 h	color rend. index	CRI	Ra 95	Ra 95	Ra 85	Ra 85	Ra 85
efficiency class	EEC	A + / A	color temperature	T	2700 K	3000 K	3000 K	3500 K	4000 K
			recommended usage		residential and public		public		
power	P	32 W	luminous flux LED	ø	2800 lm	2800 lm	3450 lm	3450 lm	3450 lm
power	P	26 W (head chrome)	luminous flux LED	ø	2250 lm	2250 lm	2750 lm	2750 lm	2750 lm

IP20

Sento sospeso
lighting effects





Sento D LED

directed light in both directions
beam angle approx. 80°

insert:	lens	
	lens	
luminous flux:	high color 32 W	2150 lm
	high flux 32 W	2650 lm
	head chrome	
	high color 26 W	1730 lm
	high flux 26 W	2110 lm





Sento E LED

diffuse up light
directed down light
beam angle approx. 80°

insert:	diffusor glass	
	lens	
luminous flux:	high color 32 W	2010 lm
	high flux 32 W	2480 lm
	head chrome	
	high color 26 W	1620 lm
	high flux 26 W	1970 lm

Sento sospeso up
article numbers

suspended luminaires with double-sided light output
version fix cable length adjustable when mounting, max. 350 cm
version variable continuous height adjustment, 50 – 200 cm
head ø 123 mm, H 72 mm

power-compensated fading-function: the full light output can be drawn in any desired ratio from one side to the other via gesture control

incl. »next generation« LEDs, total power 32 W (chrome 26 W), operation by »touchless control« (at the head, up- / downlight controllable separately), or with dimmable power supply unit externally *

color versions head / base	**color code**
chrome (26 W)	C
matt chrome	M
glossy white	B
matt white	W

base version trimless: W

with integrated converter for surface-mount installation on solid ceiling, through-wiring possible, dimmable via trailing-edge phase cut dimmer *
multiple luminaires can not be synced
base fix ø 118 mm, H 38 mm
base variable ø 118 mm, H 62 mm

fix



variable

lighting effects		high color CRI 95, 2700 K	high color CRI 95, 3000 K
lighting effects D up- / downlight each lens 80° + soft edge glass	**fix**	6E 18 1 1D 2 _	6E 18 1 1D 3 _
	variable	6E 17 1 1D 2 _	6E 17 1 1D 3 _
lighting effects E uplight diffusor glass / downlight lens 80° + soft edge glass	**fix**	6E 18 1 1E 2 _	6E 18 1 1E 3 _
	variable	6E 17 1 1E 2 _	6E 17 1 1E 3 _

please add color code
also available as »high flux« version with 3000 K / 3500 K / 4000 K

Inserts (optional)	art. no.
filter red	8K 60 2R
filter green	8K 60 2G
filter blue	8K 60 2B
filter yellow	8K 60 2Y
filter magenta	8K 60 2M
only in combination with lens	
satinised glass	8K 60 40
spot lens (recommended for use with soft edge glass)	1X 00 60 3
fresnel lens (for additional focusing use with spot lens)	8K 60 80

* compatible dimmers: www.occhio.de / dim_en